

**Air & Multipurpose**  
*General Purpose*

*Heavy Duty*  
*Push-on*

Chemical  
Transfer

Cleaning  
Equipment

Food  
*Transfer*  
*Washdown*

Marine

Material Handling

*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction & Discharge*  
*Washdown*

Welding

Coupling  
Systems

Appendix  
*Additional Products*  
*Chemical Charts*  
*General Information*  
*Minimum Run Requirements*

# GENERAL PURPOSE



<b>APPLICATION:</b>	An economical air and water hose, Horizon is for a wide range of industrial, construction and agricultural applications. Available in 200, 250, and 300 PSI working pressures.										
<b>CONSTRUCTION</b>											
<b>TUBE:</b>	Versigard® synthetic rubber, RMA Class C (Limited Oil Resistance)										
<b>COVER:</b>	Black, Red, Yellow, Green or Blue Versigard synthetic rubber										
<b>REINFORCEMENT:</b>	Spiral synthetic yarn, 2" is braided										
<b>TEMPERATURE:</b>	-40°F to 190°F (-40°C to 88°C)										
<b>PACKAGING:</b>	<table border="0"> <tr> <td>3/16"–3/4"</td> <td>500' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1"</td> <td>450' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1 1/4"</td> <td>400' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1 1/2"</td> <td>300' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>2"</td> <td>200' cartons, maximum 3 pieces, 50' increments</td> </tr> </table> <p>Coupled assemblies available in 1/4", 3/8", 1/2", and 3/4" in red.</p>	3/16"–3/4"	500' reels, maximum 3 pieces, 50' increments	1"	450' reels, maximum 3 pieces, 50' increments	1 1/4"	400' reels, maximum 3 pieces, 50' increments	1 1/2"	300' reels, maximum 3 pieces, 50' increments	2"	200' cartons, maximum 3 pieces, 50' increments
3/16"–3/4"	500' reels, maximum 3 pieces, 50' increments										
1"	450' reels, maximum 3 pieces, 50' increments										
1 1/4"	400' reels, maximum 3 pieces, 50' increments										
1 1/2"	300' reels, maximum 3 pieces, 50' increments										
2"	200' cartons, maximum 3 pieces, 50' increments										
<b>COUPLINGS:</b>	Contact fitting manufacturer for proper fitting recommendation and coupling procedure.										
<b>BRANDING:</b>	Continuous brand example 1/2" Horizon by Goodyear™ XXX psi WP.										
<b>NON-STOCK/SIZES:</b>	Refer to page 300 for special production run minimum requirements.										
<b>ORDER CODES:</b>	See next page.										

See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear.com](http://www.goodyear.com).

© 2007 The Goodyear Tire & Rubber Company.

# GENERAL PURPOSE

## HORIZON® 200

**ORDER CODES:** 536-035 (2" black) 536-040 (2" red) 569-009 (black)  
569-011 (red) 569-038 (yellow) 569-547 (blue)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
3/16	4.8	0.44	11.2	200	1.38	0.08	0.12
1/4	6.4	0.50	12.7	200	1.38	0.09	0.13
5/16	7.9	0.58	14.7	200	1.38	0.12	0.18
3/8	9.5	0.67	17.0	200	1.38	0.15	0.22
1/2	12.7	0.81	20.6	200	1.38	0.20	0.30
5/8	15.9	0.97	24.6	200	1.38	0.27	0.40
3/4	19.1	1.12	28.5	200	1.38	0.34	0.51
1	25.4	1.44	36.8	200	1.38	0.54	0.80
1 1/4	31.8	1.73	44.0	200	1.38	0.75	1.12
1 1/2	38.1	1.98	50.3	200	1.38	0.86	1.28
2	50.8	2.50	63.5	200	1.38	1.16	1.73

## HORIZON® 250

**ORDER CODES:** 569-010 (black) 569-012 (red) 569-039 (yellow)  
569-506 (green) 569-548 (blue)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
1/4	6.4	0.53	13.5	250	1.72	0.11	0.16
5/16	7.9	0.59	15.0	250	1.72	0.13	0.19
3/8	9.5	0.70	17.8	250	1.72	0.17	0.25
1/2	12.7	0.84	21.3	250	1.72	0.22	0.33
5/8	15.9	0.98	24.9	250	1.72	0.27	0.40
3/4	19.1	1.14	29.0	250	1.72	0.35	0.52

## HORIZON® 300

**ORDER CODES:** 569-516 (yellow) 569-557 (red) 569-560 (green)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
1/4	6.4	0.53	13.5	300	2.07	0.10	0.15
3/8	9.5	0.70	17.8	300	2.07	0.17	0.25
1/2	12.7	0.84	21.3	300	2.07	0.22	0.33
3/4	19.1	1.15	29.2	300	2.07	0.37	0.55
1	25.4	1.48	37.3	300	2.07	0.58	0.86

**Air & Multipurpose**  
*General Purpose*  
*Heavy Duty*  
*Push-on*

Chemical  
Transfer

Cleaning  
Equipment

Food  
*Transfer*  
*Washdown*

Marine

Material Handling  
*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction & Discharge*  
*Washdown*

Welding

Coupling  
Systems

Appendix  
*Additional Products*  
*Chemical Charts*  
*General Information*  
*Minimum Run Requirements*



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear.com](http://www.goodyear.com).

© 2007 The Goodyear Tire & Rubber Company.