

Air & Multipurpose
General Purpose

Heavy Duty
Push-on

GENERAL PURPOSE

HORIZON®



APPLICATION:	An economical air and water hose, Horizon is for a wide range of industrial, construction and agricultural applications. Available in 200, 250, and 300 PSI working pressures.										
CONSTRUCTION											
TUBE:	Versigard® synthetic rubber, RMA Class C (Limited Oil Resistance)										
COVER:	Black, Red, Yellow, Green or Blue Versigard synthetic rubber										
REINFORCEMENT:	Spiral synthetic yarn, 2" is braided										
TEMPERATURE:	-40°F to 190°F (-40°C to 88°C)										
PACKAGING:	<table border="0"> <tr> <td>3/16"–3/4"</td> <td>500' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1"</td> <td>450' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1 1/4"</td> <td>400' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>1 1/2"</td> <td>300' reels, maximum 3 pieces, 50' increments</td> </tr> <tr> <td>2"</td> <td>200' cartons, maximum 3 pieces, 50' increments</td> </tr> </table> <p>Coupled assemblies available in 1/4", 3/8", 1/2", and 3/4" in red.</p>	3/16"–3/4"	500' reels, maximum 3 pieces, 50' increments	1"	450' reels, maximum 3 pieces, 50' increments	1 1/4"	400' reels, maximum 3 pieces, 50' increments	1 1/2"	300' reels, maximum 3 pieces, 50' increments	2"	200' cartons, maximum 3 pieces, 50' increments
3/16"–3/4"	500' reels, maximum 3 pieces, 50' increments										
1"	450' reels, maximum 3 pieces, 50' increments										
1 1/4"	400' reels, maximum 3 pieces, 50' increments										
1 1/2"	300' reels, maximum 3 pieces, 50' increments										
2"	200' cartons, maximum 3 pieces, 50' increments										
COUPLINGS:	Contact fitting manufacturer for proper fitting recommendation and coupling procedure.										
BRANDING:	Continuous brand example 1/2" Horizon by Goodyear™ XXX psi WP.										
NON-STOCK/SIZES:	Refer to page 300 for special production run minimum requirements.										
ORDER CODES:	See next page.										

- Chemical Transfer
- Cleaning Equipment
- Food Transfer Washdown
- Marine
- Material Handling
 - Abrasives
 - Bulk Transfer
 - Cement & Concrete
- Mining
- Petroleum
 - Aircraft Fueling
 - Dispensing
 - Dock Transfer
- Spray
- Steam
- Vacuum
- Water
 - Discharge
 - Suction & Discharge
 - Washdown
- Welding
- Coupling Systems
- Appendix
 - Additional Products
 - Chemical Charts
 - General Information
 - Minimum Run Requirements

See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at www.goodyear.com.

© 2007 The Goodyear Tire & Rubber Company.

GENERAL PURPOSE

HORIZON® 200

ORDER CODES: 536-035 (2" black) 536-040 (2" red) 569-009 (black)
569-011 (red) 569-038 (yellow) 569-547 (blue)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
3/16	4.8	0.44	11.2	200	1.38	0.08	0.12
1/4	6.4	0.50	12.7	200	1.38	0.09	0.13
5/16	7.9	0.58	14.7	200	1.38	0.12	0.18
3/8	9.5	0.67	17.0	200	1.38	0.15	0.22
1/2	12.7	0.81	20.6	200	1.38	0.20	0.30
5/8	15.9	0.97	24.6	200	1.38	0.27	0.40
3/4	19.1	1.12	28.5	200	1.38	0.34	0.51
1	25.4	1.44	36.8	200	1.38	0.54	0.80
1 1/4	31.8	1.73	44.0	200	1.38	0.75	1.12
1 1/2	38.1	1.98	50.3	200	1.38	0.86	1.28
2	50.8	2.50	63.5	200	1.38	1.16	1.73

HORIZON® 250

ORDER CODES: 569-010 (black) 569-012 (red) 569-039 (yellow)
569-506 (green) 569-548 (blue)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.53	13.5	250	1.72	0.11	0.16
5/16	7.9	0.59	15.0	250	1.72	0.13	0.19
3/8	9.5	0.70	17.8	250	1.72	0.17	0.25
1/2	12.7	0.84	21.3	250	1.72	0.22	0.33
5/8	15.9	0.98	24.9	250	1.72	0.27	0.40
3/4	19.1	1.14	29.0	250	1.72	0.35	0.52

HORIZON® 300

ORDER CODES: 569-516 (yellow) 569-557 (red) 569-560 (green)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.53	13.5	300	2.07	0.10	0.15
3/8	9.5	0.70	17.8	300	2.07	0.17	0.25
1/2	12.7	0.84	21.3	300	2.07	0.22	0.33
3/4	19.1	1.15	29.2	300	2.07	0.37	0.55
1	25.4	1.48	37.3	300	2.07	0.58	0.86

Air & Multipurpose
General Purpose
Heavy Duty
Push-on

Chemical
Transfer

Cleaning
Equipment

Food
Transfer
Washdown

Marine

Material Handling
Abrasives
Bulk Transfer
Cement & Concrete

Mining

Petroleum
Aircraft Fueling
Dispensing
Dock
Transfer

Spray

Steam

Vacuum

Water
Discharge
Suction & Discharge
Washdown

Welding

Coupling
Systems

Appendix
Additional Products
Chemical Charts
General Information
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at www.goodyear.com.

© 2007 The Goodyear Tire & Rubber Company.