



# Tube Fittings & Adapters

## MORB-FJS Straight 6402-O Series



PART NO. SIZE	TUBE O.D.	B1 SAE ORB	B2 JIC	L		W	C1		C2		C1		Standard Material From Stock			
				LGTH	M.M.		HEX	HEX	M.M.	HEX	HEX	M.M.	S	FG	SS	B
6402-04-04-O	1/4	7/16-20	7/16-20	1.470	37.34	0.330	9/16	0.562	14.27	9/16	0.562	14.27	•		•	
6402-04-06-O	1/4	7/16-20	9/16-18	1.410	35.81	0.330	9/16	0.562	14.27	9/16	0.562	14.27	•		•	
6402-06-04-O	3/8	9/16-18	7/16-20	1.350	34.29	0.330	11/16	0.687	17.45	9/16	0.562	14.27	•		•	
6402-06-06-O	3/8	9/16-18	9/16-18	1.480	37.59	0.330	11/16	0.687	17.45	11/16	0.687	17.45	•		•	
6402-06-08-O	1/2	9/16-18	3/4-16	1.620	41.15	0.390	11/16	0.687	17.45	11/16	0.687	17.45	•		•	
6402-08-08-O	1/2	3/4-16	3/4-16	1.600	40.64	0.350	7/8	0.875	22.23	7/8	0.875	22.23	•		•	
6402-10-08-O	5/8	7/8-14	3/4-16	1.705	43.31	0.410	1	1.000	25.40	7/8	0.875	22.23	•		•	
6402-10-10-O	5/8	7/8-14	7/8-14	1.970	50.04	0.430	1	1.000	25.40	1	1.000	25.40	•		•	
6402-12-12-O	3/4	1 1/16-12	1 1/16-12	2.160	54.86	0.500	1 1/4	1.250	31.75	1 1/4	1.250	31.75	•		•	
6402-16-16-O	1	1 5/16-12	1 5/16-12	2.280	57.91	0.520	1 1/2	1.500	38.10	1 1/2	1.500	38.10	•		•	
6402-20-20-O	1 1/4	1 5/8-12	1 5/8-12	2.415	61.34	0.600	1 7/8	1.875	47.63	1 7/8	1.875	47.63	•		•	
6402-24-24-O	1 1/2	1 7/8-12	1 1/2-11 1/2	2.610	66.29	0.690	2 1/8	2.125	53.98	2 1/8	2.125	53.98	•		•	
6402-32-32-O	2	2 1/2-12	2-11 1/2	2.905	73.79	0.845	2 3/4	2.75	69.85	2 7/8	2.875	73.03	•		•	

## FORB-MP Straight 6404 Series



PART NO. SIZE	TUBE O.D.	B1 SAE ORB	A2 NPTF	L		W	C		C	M.M.	Standard Material From Stock			
				LGTH	M.M.		HEX	HEX			M.M.	S	FG	SS
NEW 6404-03-06											•			
6404-04-02	1/4	7/16-20	1/8-27	1.130	28.70	1.000	11/16	0.687	17.45	•		•		
6404-04-04	1/4	7/16-20	1/4-18	1.320	33.53	0.750	11/16	0.687	17.45	•		•		
6404-04-06	1/4	7/16-20	3/8-18	1.130	28.70	1.000	11/16	0.687	17.45	•		•		
6404-05-02	5/16	1/2-20	1/8-27	1.370	34.80	0.800	3/4	0.750	19.05	•		•		
6404-05-04	5/16	1/2-20	1/4-18	1.390	35.31	0.800	3/4	0.750	19.05	•		•		
6404-05-06	5/16	1/2-20	3/8-18	1.380	35.05	0.800	3/4	0.750	19.05	•		•		
6404-06-04	3/8	9/16-18	1/4-18	1.390	35.31	0.984	7/8	0.875	22.23	•		•		
6404-06-06	3/8	9/16-18	3/8-18	1.395	35.43	0.800	7/8	0.875	22.23	•		•		
6404-06-08	3/8	9/16-18	1/2-14	1.420	36.07	0.650	7/8	0.875	22.23	•		•		
NEW 6404-08-04											•			
6404-08-06	1/2	3/4-16	3/8-18	1.500	38.10	0.937	1	1.000	25.40	•		•		
6404-08-08	1/2	3/4-16	1/2-14	1.700	43.18	0.937	1	1.000	25.40	•		•		
6404-08-12	1/2	3/4-16	3/4-14	1.690	42.93	0.930	1 1/8	1.125	28.58	•		•		
6404-10-06	5/8	7/8-14	3/8-18	1.620	41.15	1.060	1 1/4	1.250	31.75	•		•		
6404-10-08	5/8	7/8-14	1/2-14	1.820	46.23	1.062	1 1/4	1.250	31.75	•		•		
6404-10-12	5/8	7/8-14	3/4-14	1.720	43.69	0.960	1 1/8	1.125	28.58	•		•		
6404-12-08	3/4	1 1/16-12	1/2-14	1.960	49.78	1.210	1 3/8	1.375	34.93	•		•		
6404-12-12	3/4	1 1/16-12	3/4-14	1.960	49.78	1.218	1 3/8	1.375	34.93	•		•		
6404-14-12	7/8	1 3/16-12	3/4-14	2.040	51.82	1.218	1 1/2	1.500	38.10	•		•		
6404-16-12	1	1 5/16-12	3/4-14	2.060	52.32	1.300	1 5/8	1.625	41.28	•		•		
6404-16-16	1	1 5/16-12	1-11 1/2	2.220	56.39	1.218	1 5/8	1.625	41.28	•		•		
6404-16-20	1	1 5/16-12	1 1/4-11 1/2	1.900	48.26	0.930	2	2.000	50.80	•		•		
6404-16-24	1 1/4	1 5/16-12	1 1/2-11 1/2	1.9	48.26	.906	2	2.000	50.80	•		•		
6404-20-16	1 1/4	1 5/8-12	1-11 1/2	2.210	56.13	1.250	2	2.000	50.80	•		•		
6404-20-20	1 1/4	1 5/8-12	1 1/4-11 1/2	2.340	59.44	1.281	2 1/8	2.125	53.98	•		•		
6404-24-24	1 1/2	1 7/8-12	1 1/2-11 1/2	2.300	58.42	1.281	2 1/4	2.250	57.15	•		•		
6404-32-32	2	2 1/2-12	2-11 1/2	2.660	67.56	1.281	2 7/8	2.875	73.03	•		•		