


# D03 Standard Flow Parallel Circuit Manifold



No. of stations	* 01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16
"A" length (code 2 spa.) inch [mm]	2.13 [54.0]	4.25 [108.0]	6.38 [162.1]	8.50 [215.9]	10.63 [270.0]	12.75 [323.9]	14.88 [378.0]	17.00 [431.8]	19.13 [485.9]	21.25 [539.8]	23.38 [593.9]	25.50 [647.7]	27.63 [701.8]	29.75 [755.7]	31.88 [809.8]	34.00 [863.6]
apx. weight alum lb [kg]	3 [1]	4 [2]	6 [3]	8 [4]	9 [4]	11 [5]	12 [5]	14 [6]	16 [7]	18 [8]	20 [9]	21 [10]	22 [10]	24 [11]	26 [12]	27 [12]
apx. weight iron lb [kg]	5 [2]	9 [4]	13 [6]	17 [8]	21 [10]	26 [12]	30 [14]	34 [15]	38 [17]	42 [19]	47 [21]	51 [23]	55 [25]	59 [27]	63 [29]	68 [31]
"A" length (code 4 spa.) inch [mm]	--	6.13 [155.7]	10.13 [257.3]	14.13 [358.9]	18.13 [460.5]	22.13 [562.1]	26.13 [663.7]	30.13 [765.3]								
apx. weight alum lb [kg]	--	6 [3]	9 [4]	12 [5]	15 [7]	19 [9]	22 [10]	25 [11]								
apx. weight iron lb [kg]	--	12 [5]	20 [9]	28 [13]	36 [16]	45 [20]	53 [24]	57 [26]								

Port code	Valve mtg.	Manifold mtg.
P, S	#10-24 UNC x 0.63 [16] DP	0.31-18 UNC x 0.44 [11.1] DP
B, M, T	M5 ISO 6H x 0.63 [16] DP	M8 ISO 6H x 0.44 [11.1] DP

\* Length of 01 station with relief cavity is 3.00 [76.2]. Gauge port not available on 01 station.

Specifications, descriptions, and dimensional data are subject to correction or change without notice or incurring obligation. Download latest catalog page revisions at [www.damanifolds.com](http://www.damanifolds.com).

## Ordering Information

Material	Valve Pattern	Circuit	No. of Stations	Valve Spacing	Port Threads	Options																																																																		
<table border="1"> <thead> <tr> <th colspan="2">Material</th> </tr> </thead> <tbody> <tr> <td><b>A</b></td> <td>Aluminum - 6061-T6 3000† psi • 20.7 MPa</td> </tr> <tr> <td><b>D</b></td> <td>Ductile Iron - D4512 5000† psi • 34.5 MPa</td> </tr> </tbody> </table> <p>† Working pressure should be considered in accordance with ISO 4413 to determine appropriate material type.</p>	Material		<b>A</b>	Aluminum - 6061-T6 3000† psi • 20.7 MPa	<b>D</b>	Ductile Iron - D4512 5000† psi • 34.5 MPa	<table border="1"> <thead> <tr> <th colspan="2">Valve Pattern</th> </tr> </thead> <tbody> <tr> <td><b>D03</b></td> <td>ISO 4401-03-02 NFPA T3.5.1-D03 See Tech Information</td> </tr> </tbody> </table>	Valve Pattern		<b>D03</b>	ISO 4401-03-02 NFPA T3.5.1-D03 See Tech Information	<table border="1"> <thead> <tr> <th colspan="2">Circuit</th> </tr> </thead> <tbody> <tr> <td><b>P</b></td> <td>Parallel Circuit Standard Flow</td> </tr> </tbody> </table>	Circuit		<b>P</b>	Parallel Circuit Standard Flow	<table border="1"> <thead> <tr> <th colspan="2">No. of Stations</th> </tr> </thead> <tbody> <tr> <td colspan="2">Aluminum</td> </tr> <tr> <td><b>01...16</b></td> <td>Available with spacing code 2</td> </tr> <tr> <td><b>02...08</b></td> <td>Available with spacing code 4</td> </tr> <tr> <td colspan="2">Ductile Iron</td> </tr> <tr> <td><b>01...16</b></td> <td>Available with spacing code 2</td> </tr> <tr> <td><b>02...08</b></td> <td>Available with spacing code 4</td> </tr> </tbody> </table>	No. of Stations		Aluminum		<b>01...16</b>	Available with spacing code 2	<b>02...08</b>	Available with spacing code 4	Ductile Iron		<b>01...16</b>	Available with spacing code 2	<b>02...08</b>	Available with spacing code 4	<table border="1"> <thead> <tr> <th colspan="2">Valve Spacing</th> </tr> </thead> <tbody> <tr> <td><b>2</b></td> <td>2.13 inch 54.0 mm</td> </tr> <tr> <td><b>4</b></td> <td>4.00 inch 101.6 mm</td> </tr> </tbody> </table>	Valve Spacing		<b>2</b>	2.13 inch 54.0 mm	<b>4</b>	4.00 inch 101.6 mm	<table border="1"> <thead> <tr> <th colspan="4">Port Threads</th> </tr> </thead> <tbody> <tr> <th>P</th> <th>P &amp; T</th> <th>A &amp; B</th> <th>GA</th> </tr> <tr> <td><b>P</b></td> <td>NPTF • ANSI B1.20.3</td> <td>0.50</td> <td>0.25</td> </tr> <tr> <td><b>S</b></td> <td>SAE • ISO 11926</td> <td>-10</td> <td>-6</td> </tr> <tr> <td><b>B</b></td> <td>BSPP • ISO 1179</td> <td>0.50</td> <td>none</td> </tr> <tr> <td><b>M</b></td> <td>ISO • ISO 6149</td> <td>M22</td> <td>none</td> </tr> <tr> <td><b>T</b></td> <td>BSPT • ISO 7</td> <td>0.50</td> <td>0.38</td> </tr> </tbody> </table>	Port Threads				P	P & T	A & B	GA	<b>P</b>	NPTF • ANSI B1.20.3	0.50	0.25	<b>S</b>	SAE • ISO 11926	-10	-6	<b>B</b>	BSPP • ISO 1179	0.50	none	<b>M</b>	ISO • ISO 6149	M22	none	<b>T</b>	BSPT • ISO 7	0.50	0.38	<table border="1"> <thead> <tr> <th colspan="2">Options</th> </tr> </thead> <tbody> <tr> <td colspan="2">See next page for available options and ordering codes.</td> </tr> </tbody> </table>	Options		See next page for available options and ordering codes.	
Material																																																																								
<b>A</b>	Aluminum - 6061-T6 3000† psi • 20.7 MPa																																																																							
<b>D</b>	Ductile Iron - D4512 5000† psi • 34.5 MPa																																																																							
Valve Pattern																																																																								
<b>D03</b>	ISO 4401-03-02 NFPA T3.5.1-D03 See Tech Information																																																																							
Circuit																																																																								
<b>P</b>	Parallel Circuit Standard Flow																																																																							
No. of Stations																																																																								
Aluminum																																																																								
<b>01...16</b>	Available with spacing code 2																																																																							
<b>02...08</b>	Available with spacing code 4																																																																							
Ductile Iron																																																																								
<b>01...16</b>	Available with spacing code 2																																																																							
<b>02...08</b>	Available with spacing code 4																																																																							
Valve Spacing																																																																								
<b>2</b>	2.13 inch 54.0 mm																																																																							
<b>4</b>	4.00 inch 101.6 mm																																																																							
Port Threads																																																																								
P	P & T	A & B	GA																																																																					
<b>P</b>	NPTF • ANSI B1.20.3	0.50	0.25																																																																					
<b>S</b>	SAE • ISO 11926	-10	-6																																																																					
<b>B</b>	BSPP • ISO 1179	0.50	none																																																																					
<b>M</b>	ISO • ISO 6149	M22	none																																																																					
<b>T</b>	BSPT • ISO 7	0.50	0.38																																																																					
Options																																																																								
See next page for available options and ordering codes.																																																																								