


MODEL CFF Through port with gauge port

CAVITY: T-3A



sunhydraulics.com/model/CEE



TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Through port with gauge port
Mounting Hole Thread	.250-20 UNC - 2B in.
Mounting Hole Depth	.50 in.
Mounting Hole Quantity	2
Open Cavities	1
Cavity	T-3A
Port Size	1" NPTF
Model Weight	3.44 lb.

CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N, Chem.

Black

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
CEE, /10, /11	Ports 1 & 2: 1" NPTF; Gage Ports: 1/4" NPTF;

CONFIGURATION OPTIONS Model Code Example: CEE/S

MODIFIER (/S)

/S 65-45-12 Ductile Iron, Buna-N, Chem. Black

6061-T651 Aluminum, Buna-N

/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

© 2020 Sun Hydraulics