


CONFIGURATION

X	Control	Not Adjustable
Z	Cracking Pressure	1 psi (0,07 bar)
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating



Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-8A
Series	P
Capacity	5 gpm
Valve Hex Size	7/8 in.
Valve Installation Torque	20 - 25 lbf ft
Seal kit - Cartridge	Buna: 990608007
Seal kit - Cartridge	EPDM: 990608014
Seal kit - Cartridge	Viton: 990608006
Model Weight	0.11 lb.

CONFIGURATION OPTIONS

Model Code Example: **CXAAXZN**

CONTROL	(X)	CRACKING PRESSURE	(Z)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		Z 1 psi (0,07 bar)		N Buna-N		Standard Material/Coating
		B 15 psi (1 bar)		E EPDM		/AP Stainless Steel, Passivated
		F 100 psi (7 bar)		V Viton		/LH Mild Steel, Zinc-Nickel

TECHNICAL FEATURES

- Check valves offer extremely low leakage rates with a maximum leakage of less than 1 drop per minute (0,07 cc/min).
- Will accept 5000 psi (350 bar) at ports 1 and 2.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

