


Sequence, On P port 3 to T



### TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 03
Body Features	On P, port 3 to T
Stack Height	1.75 in.
Seal Plate Included (see notes)	Yes
Open Cavities	1
Cavity	T-11A
Port Size	1/4" NPTF
Model Weight	1.68 lb.

### CONFIGURATION

*NY* Modifier 65-45-12 Ductile Iron, Viton, Chem. Black

### NOTES

- Stack height value in technical data table includes seal retainer plate.
- Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

## PORT DESIGNATORS

Modifiers	Ports
EBW, /10, /11, /15, /16, /S, /S3, /V, /Y, /Y3	Gage Port (Plugged): 1/4" NPTF;
EBW/1A, /1B, /1F, /1G, /M, /T, /T3, /W, /W3, /Z	Gage Port (Plugged): 1/4" BSPP;

## INCLUDED COMPONENTS

Part	Description	Quantity
340-003	Pipe Plug	1
500-101-012	O-Ring	4
700-002	Seal Plate	1
811-001-006	Pin	1
850-004-218	Plug	1

## CONFIGURATION OPTIONS

Model Code Example: EBW/Y

MODIFIER	(Y)
<b>/Y</b> 65-45-12 Ductile Iron, Viton, Chem. Black	
6061-T651 Aluminum, Buna-N	
<b>/11</b> 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I	
<b>/10</b> 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II	
<b>/V</b> 6061-T651 Aluminum, Viton	
<b>/16</b> 6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I	
<b>/15</b> 6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II	
<b>/M</b> 6061-T651 Aluminum, Metric, Buna-N	
<b>/1B</b> 6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I	
<b>/1A</b> 6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II	
<b>/Z</b> 6061-T651 Aluminum, Metric, Viton	
<b>/1G</b> 6061-T651 Aluminum, Metric, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I	
<b>/1F</b> 6061-T651 Aluminum, Metric, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II	
<b>/S</b> 65-45-12 Ductile Iron, Buna-N, Chem. Black	
<b>/S3</b> 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer	
<b>/Y3</b> 65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer	
<b>/T</b> 65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black	
<b>/T3</b> 65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer	
<b>/W</b> 65-45-12 Ductile Iron, Metric, Viton, Chem. Black	
<b>/W3</b> 65-45-12 Ductile Iron, Metric, Viton, Trivalent Clear Zinc with Top Sealer	