



## CONFIGURATION

<b>H</b>	Control	Calibrated Handknob with Detent Lock
<b>A</b>	Adjustment Range	.2 - 12 gpm (0,8 - 45 L/min.)
<b>V</b>	Seal Material	Viton
<b>(none)</b>	Material/Coating	Standard Material/Coating

Fully adjustable, pressure-compensated flow controls with reverse-flow check provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. They are infinitely adjustable from nearly closed up to the maximum flow. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-5A
Series	2
Capacity	12 gpm
Maximum Operating Pressure	5000 psi
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Valve Hex Size	1 1/8 in.
Valve Installation Torque	45 - 50 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	EPDM: 990203014
Seal kit - Cartridge	Viton: 990203006
Model Weight	0.62 lb.

**NOTES** For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

## CONFIGURATION OPTIONS

**Model Code Example: FDCBHAV**

CONTROL	(H) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(V) MATERIAL/COATING
<b>H</b> Calibrated Handknob with Detent Lock	<b>A</b> .2 - 12 gpm (0,8 - 45 L/min.)	<b>V</b> Viton	Standard Material/Coating
<b>L</b> Standard Screw Adjustment	<b>B</b> .2 - 3 gpm (0,8 - 11 L/min.)	<b>N</b> Buna-N	/LH Mild Steel, Zinc-Nickel
<b>K</b> Handknob		<b>E</b> EPDM	
<b>Y</b> Tri-Grip Handknob			

## TECHNICAL FEATURES

- All 2-port flow control cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size). However, cartridge extension dimensions from the mounting surface may vary.
- A balanced adjustment mechanism allows for easy adjustment even at high pressures.
- The sharp-edged orifice design minimizes flow variations due to viscosity changes.
- Minimum leakage is .2 gpm (0,8 L/min) when the adjustment mechanism is turned to the shut-off position.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.

## PERFORMANCE CURVES

