



### CONFIGURATION

<b>X</b>	Control	Not Adjustable
<b>A</b>	Setting Range	Fixed Orifice .1 - 3 gpm (0,4 - 11 L/min.)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	Standard Material/Coating

Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-162A
Series	0
Capacity	3 gpm
Maximum Operating Pressure	5000 psi
Valve Hex Size	3/4 in.
Valve Installation Torque	20 - 25 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	EPDM: 990162014
Seal kit - Cartridge	Polyurethane: 990162002
Seal kit - Cartridge	Viton: 990162006
Model Weight	0.16 lb.

### CONFIGURATION OPTIONS

**Model Code Example: FXBAXAN**

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>A</b> Fixed Orifice .1 - 3 gpm (0,4 - 11 L/min.)	<b>N</b> Buna-N	Standard Material/Coating
<b>L</b> Tuning Adjustment		<b>E</b> EPDM	/AP Stainless Steel, Passivated
<b>K</b> Handknob		<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel

### TECHNICAL FEATURES

- Customer must specify a flow rating. Factory set flow ratings are within +/- 15% of the requested setting.
- The tuneable control option provides +/- 20% variation from the nominal factory pre-set flow. Turn the adjustment clockwise to increase.
- The sharp-edged orifice design minimizes flow variations due to viscosity changes.
- All 2-port flow control cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size). However, cartridge extension dimensions from the mounting surface may vary.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

### PERFORMANCE CURVES

