

## **Product Specifications**



## P550335 LUBE FILTER, SPIN-ON FULL FLOW

## Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

## Attributes

Outer Diameter	2.99 inch (76 mm)
Thread Size	3/4-16
Length	3.39 inch (86 mm)
Gasket OD	2.76 inch (70 mm)
Gasket ID	2.36 inch (60 mm)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	11 psi (0.75 bar)
Bypass Valve Setting HR	17 psi (1.2 bar)
Media Type	Cellulose
Collapse Burst	100 psi (6.9 bar)
Туре	Full-Flow
Style	Spin-On
Packaged Dimensions	
Packaged Length	3 IN
Packaged Width	3 IN
Packaged Height	3.3IN
Packaged Weight	0.685 LB
Packaged Volume	0.0172 FT3
Other Information	
Country of Origin	Colombia
NMFC Code	069100-10
HTS Code	8421230000
UPC Code	742330042236

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.