



## P550425

### LUBE FILTER, SPIN-ON BYPASS

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Offer increased efficiency in capturing smaller particles.

#### Attributes

Outer Diameter	4.29 inch (109 mm)
Thread Size	1 3/8-16 UN
Length	10.35 inch (263 mm)
Gasket OD	3.98 inch (101 mm)
Gasket ID	3.62 inch (92 mm)
Efficiency 50%	5 micron
Efficiency 99%	21 micron
Efficiency Test Std	SAE J806
Media Type	Cellulose
Collapse Burst	120 psi (8.3 bar)

Type	Full-Flow
Style	Spin-On
Primary Application	VOLVO 4775565

---


#### Packaged Dimensions

Packaged Length	0.35 FT
Packaged Width	0.35 FT
Packaged Height	0.86FT
Packaged Weight	2.34 LB
Packaged Volume	0.1051 FT3

---

#### Other Information

Country of Origin	United States
NMFC Code	069095-02
HTS Code	8421230000
UPC Code	742330107744

Proposition 65 Notice for California:   
WARNING

This product can expose you to chemicals including Formaldehyde, which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.