

Product Specifications



P552100 LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	4.65 inch (118 mm)
Thread Size	1 5/8-12 UN
Length	10.24 inch (260 mm)
Gasket OD	4.33 inch (110 mm)
Gasket ID	3.86 inch (98 mm)
Efficiency 99%	21 micron
Efficiency Test Std	SAE J1858
Media Type	Cellulose
Collapse Burst	149 psi (10.3 bar)

Туре	Full-Flow
Style	Spin-On
Primary Application	DETROIT DIESEL 23518480
Packaged Dimensions	
Packaged Length	4.65 IN
Packaged Width	4.65 IN
Packaged Height	10.1IN
Packaged Weight	2.71 LB
Packaged Volume	0.1264 FT3
Other Information	
Country of Origin	United States
NMFC Code	069095-02
HTS Code	8421230000
UPC Code	742330044094
Proposition 65 Notice for California: 🛆 WARNING	This product can expose you to chemicals including Formaldehyde, which are known to the State of California to cause cancer. For more information go to <u>www.P65Warnings.ca.gov</u> .

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.