

# Product Specifications



## P777868

## AIR FILTER, PRIMARY RADIALSEAL

Why Choose Donaldson RadialSeal™ Filters?

Reliable, leak- resistant Radial Seal™ keeps filters in place – even under heavy vibration.

- High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.
- Corrosion resistant, coated steel liners support media during operation and help maximize airflow.
- Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.

#### **Attributes**

Outer Diameter	12.34 inch (313.4 mm)
Inner Diameter	6.99 inch (177.6 mm)
Length	20.63 inch (524 mm)
Overall Length	20.39 inch (517.8 mm)
Efficiency	99.9
Efficiency Test Std	ISO 5011
Family	FRG
Primary Application	TEREX 15270188
Туре	Primary

Style	Radialseal
Brand	RadialSeal™
Media Type	Cellulose
Packaged Dimensions	
Packaged Length	12.8 IN
Packaged Width	12.8 IN
Packaged Height	22.3IN
Packaged Weight	9.1 LB
Packaged Volume	2.1475 FT3
Other Information	

### Other Information

21310000
21310000
2330081792
s product can expose you to chemicals luding Styrene, which are known to the te of California to cause cancer. For more prmation go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
s lı

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.