



in (mm)

This cavity plug allows all ports to remain open.

CONFIGURATION

X	Control	-
X	Adjustment Range	-
V	Seal Material	Viton
(none)	Material/Coating	Standard Material/Coating

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-19A
Series	4
Maximum Operating Pressure	3000 psi
Port Configuration	3 Port
Valve Hex Size	1 5/8 in.
Valve Installation Torque	350 - 375 lbf ft
Seal kit - Cartridge	Buna: 990019007
Seal kit - Cartridge	EPDM: 990019014
Seal kit - Cartridge	Polyurethane: 990019002
Seal kit - Cartridge	Viton: 990019006
Model Weight	1.39 lb.

CONFIGURATION OPTIONS
Model Code Example: XJOBXXV

CONTROL	(X)	ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(V)	MATERIAL/COATING
X -		X -		V Viton E EPDM N Buna-N		Standard Material/Coating /AP Stainless Steel, Passivated

TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.