



These cavity plugs can be used for both two-port and four-port cavities and allow all ports to remain connected.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-18A & T-34A
Series	4
Maximum Operating Pressure	5000 psi
Port Configuration	2 Port / 4 Port
Valve Hex Size	1 5/8 in.
Valve Installation Torque	350 - 375 lbf ft
Seal kit - Cartridge	Buna: 990018007
Seal kit - Cartridge	EPDM: 990018014
Seal kit - Cartridge	Viton: 990018006
Model Weight	1.28 lb.

**CONFIGURATION**

<b>X</b>	Control	-
<b>X</b>	Adjustment Range	-
<b>V</b>	Seal Material	Viton
<b>(none)</b>	Material/Coating	Standard Material/Coating

**CONFIGURATION OPTIONS**

**Model Code Example: XKOAXXV**

<b>CONTROL</b>	<b>(X) ADJUSTMENT RANGE</b>	<b>(X) SEAL MATERIAL</b>	<b>(V) MATERIAL/COATING</b>
<b>X -</b>	<b>X -</b>	<b>V</b> Viton E EPDM N Buna-N	<b>Standard Material/Coating</b> /AP Stainless Steel, Passivated

**TECHNICAL FEATURES**

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.