



CONFIGURATION

| | | |
|---------------|------------------|---------------------------|
| X | Control | - |
| X | Adjustment Range | - |
| N | Seal Material | Buna-N |
| (none) | Material/Coating | Standard Material/Coating |

This cavity plug allows all ports to remain open.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|-------------------------|
| Cavity | T-162A |
| Series | 0 |
| Maximum Operating Pressure | 5000 psi |
| Port Configuration | 2 Port |
| Valve Hex Size | 3/4 in. |
| Valve Installation Torque | 20 - 25 lbf ft |
| Seal kit - Cartridge | Buna: 990162007 |
| Seal kit - Cartridge | EPDM: 990162014 |
| Seal kit - Cartridge | Polyurethane: 990162002 |
| Seal kit - Cartridge | Viton: 990162006 |
| Model Weight | 0.13 lb. |

CONFIGURATION OPTIONS

Model Code Example: XZOAXXN

| CONTROL | (X) ADJUSTMENT RANGE | (X) SEAL MATERIAL | (N) MATERIAL/COATING |
|------------|----------------------|--------------------------------------|--|
| X - | X - | N Buna-N E EPDM V Viton | Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel |

TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.